

VOX-150-TS / VOX-150L-TS



FEATURES

- 15" TFT LCD (AU-G150XG01 / AU-G150XG03V5)
- VMXP-6427 3.5" CPU Module
- 512MB/1GB Memory Support
- 4-Wire Resistive Touch Screen
- Metal Chassis
- AC/DC Power Adapter



◀ VMXP-6427



<http://www.icop.com.tw/product/VMXP-6427.html>

SPECIFICATION

Model Name	VOX-150-TS	VOX-150L-TS	
LCD Display	Type	XVGA	
	Size	15"	
	Resolution	1024x768	
	Colors	262,144	
	View Angle (L/R/U/D)	80 / 80 / 70 / 60	
	Brightness	350 cd/m ²	250 cd/m ²
	Backlight Life / Type	50,000 / CCFL	25,000 / LED
	Contrast Ratio	700:1	
CPU	DMP Vortex86MX+ 800MHz		
Cache	L1:16KB I-Cache, 16KB D-Cache / L2: 256KB Cache		
Memory	512MB / 1GB Memory Onboard		
Watchdog Timer	Software Programmable from 30.5u to 512 Seconds x 2 Sets		
Serial Port	RS-232 / 422 / 485 x 1, RS-232 x 6		
USB Ports	USB Ports (Ver2.0) x 2		
Ethernet	Integrated 10/100Mbps Ethernet		
Audio	CM119 Audio Controller / HD Audio-Realtek ALC262 CODEC		
Flash Disk Support	Onboard 4MB Flash Disk (Optional) / EmbedDisk Module / Compact Flash Type I/II (Optional)		
Touch Screen Type	Resistive		
Power Requirement	5VDC, 12VDC		
Power Consumption	47W		
Operating Temperature	0 ~ +50 °C (32 ~ +122 °F)		
Dimensions (WxHxD mm)	368 x 278 x 45.5 (14.5" x 10.9" x 1.8")		
Operating System	DOS, Linux, Windows CE, Windows XP Embedded		

